

# TCHM 65 Centrifugal Pump



200 Newsome Drive  
Yorktown, VA 23693  
1-800-535-4243  
www.Travaini.com



<b>Head Capacity</b>	10 to 300 Feet
<b>Capacity</b>	Up to 810 USGPM
<b>Features</b>	Closed impeller design for use with clean or muddy liquids
<b>Shaft Sealing</b>	Mechanical seal (standard) Double mechanical seal Stuffed packing box
<b>Options</b>	Bareshaft pump Coupled to electric motor Monoblock
<b>Temperature</b>	GS & RA: -20°C-280°C A3, HC, & DU: -40°C-280°C

## Technical Data

PUMP TYPE		TCHM65-125		TCHM65-160		TCHM65-200		TCHM65-250
Head, max	Ft	31	125	50	200	73	300	118
Capacity, max	GPM	310	675	390	750	400	810	375
Speed	RPM	1750	3500	1750	3500	1750	3500	1750

## Standard Materials of Construction\*\*

Part No.	Description	GS	RA	A3	HC	DU
102	Pump casing	Ductile iron			Hastelloy C	ASTM-CN7M
135	Wear plates	-	Cast iron			
161	Casing cover	Ductile iron				
210	Shaft	Stainless steel AISI 316			Incoloy 825	
230	Impeller				ASTM-CN7M	
330	Bearing housing	Cast iron				
524	Shaft sleeve	Stainless steel AISI 316		Hastelloy C	Incoloy 825	

## Model Designation

<u>TCHM65-200 A/1X-C/A3</u>	
T	Travaini manufacturer
C	Monostage centrifugal pump
H	Closed impeller
M	Monoblock Construction
65	Discharge flange size (mm)
200	Nominal diameter of impeller (mm)
A	Modification of hydraulic design
1X	Constructive project number
C	Shaft sealing: C—Single mechanical seal 2C— Double mechanical seal
A3	Materials of construction

\*\*Special materials available upon request

--For further information please consult Travaini Pumps USA.